

Description

HZ-THZ BT-0006-6 is a SMA bias tee (also known as bias T) that operates from 10 MHz to 6 GHz with a bias rating of 100 VDC and 4000 mA. This bias tee is configured with SMA inputs on the RF ports and SMA on the bias port. BT-0006-6 SMA bias T offers good electrical performance featuring 0.8 dB insertion loss and 30 dB isolation. Bias tees are typically used to inject a DC signal into an RF path such as when biasing an amplifier or any other active device, supplying power to the connected output without disrupting the RF signal. They can also be used as DC returns to provide a ground return path for the input device or DC blocks to prevent direct current signals from flowing through the output device. HZ-THZ bias tees are available in various connector configurations over different frequency bands to fit your needs, all of which shipped worldwide the same day.

Features

- Broadband: 10 MHz to 6 GHz
- Low Insertion Loss
- Isolation 30 dB
- 4000 mA / 100 VDC Bias
- RF Power 10 W Max

Applications

- Amplifier Biasing
- Coax
- Wireless Systems
- DC Return / Block
- Test and Measurement
- Transmitting Power With a Single
- Communication Systems

Configuration

| | |
|----------------------|------------|
| RF Port Connector | SMA Female |
| DC/RF Port Connector | SMA Female |
| DC Port Connector | SMA Female |

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-----------------------|---------|---------|---------|-------|
| Frequency Range | 0.01 | | 6 | GHz |
| Impedance | | 50 | | Ohms |
| VSWR | | | 1.5 | : 1 |
| Insertion Loss | | 0.8 | 1.5 | dB |
| RF to Bias Isolation | | 30 | | dB |
| DC Current | | | 4000 | mA |
| DC Voltage | | | 100 | Vdc |
| RF Power | | | 10 | W |
| Operating Temperature | -55 | | +105 | °C |
| Storage Temperature | -55 | | +125 | °C |

Electrical Specification Notes:

Values at +25°C, sea level.

Mechanical Specifications

Size

| | |
|--------|--------------------|
| Length | 1.29 in [32.80 mm] |
| Width | 0.71 in [18.00 mm] |
| Height | 0.55 in [14.00 mm] |

Weight 0.07 lbs [30.00 g]

Package Type Customized

Outline Drawings

Unit: mm


Tolerance: ±0.05 mm

Bias Tee

BT-0006-6

10 MHz to 6 GHz, 4000 mA and 100 VDC, SMA

HZ-THZ



How To Order

BT-0006-6

Pls send request to sales@hz-thz.com.