Bias Tee

BT-0006 7 KHz to 6 GHz, 500 mA and 50 VDC, SMA

HZ-THZ

Description

HZ-THZ BT-0006 is a SMA bias tee (also known as bias T) that operates from 7 KHz to 6 GHz with a bias rating of 50 VDC and 500 mA. This bias tee is configured with SMA inputs on the RF ports and SMA on the bias port. BT-0006 SMA bias T offers good electrical performance featuring 0.8 dB insertion loss and 30 dB isolation. Bias tees are typically used to inject a DC signal into an RF path such as when biasing an amplifier or any other active device, supplying power to the connected output without disrupting the RF signal. They can also be used as DC returns to provide a ground return path for the input device or DC blocks to prevent direct current signals from flowing through the output device. HZ-THZ bias tees are available in various connector configurations over different frequency bands to fit your needs, all of which shipped worldwide the same day.

Features

- Broadband: 7 KHz to 6 GHz
- Low Insertion Loss
- Isolation 30 dB
- 500 mA / 50 VDC Bias
- RF Power 10 W Max

Applications

- Amplifier Biasing
- Coax
- Wireless Systems
- DC Return / Block
- Test and Measurement
- Transmitting Power With a Single
- Communication Systems

Configuration

RF Port Connector	SMA Female
DC/RF Port Connector	SMA Female
DC Port Connector	SMA Female

Bias Tee

HZ-THZ

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.000007		6	GHz
Impedance		50		Ohms
VSWR			1.8	:1
Insertion Loss		0.8	1.5	dB
RF to Bias Isolation		30		dB
DC Current			500	mA
DC Voltage			50	Vdc
RF Power			10	W
Operating Temperature	-55		+105	°C
Storage Temperature	-55		+125	°C

Electrical Specification Notes:

Values at +25°C, sea level.

Mechanical Specifications


Size Length Width Height	1.49 in [37.80 mm] 1.32 in [33.60 mm] 0.39 in [10.00 mm]
Weight	0.07 lbs [30.00 g]
Package Type	Customized

Outline Drawings

Unit: mm Tolerance: ±0.05 mm **Bias Tee**

BT-0006 7 KHz to 6 GHz, 500 mA and 50 VDC, SMA





How To Order

BT-0006

Pls send request to sales@hz-thz.com.