

Description

LNA-50M1G low noise amplifier from HZ-THZ (also known as LNA) is featured in our extensive in-stock RF amplifier selection. Our connectorized low noise amplifier uses SMA connectors at 50 Ohm. HZ-THZ low noise amplifier has a minimum frequency of 50 MHz and maximum frequency of 1 GHz. The significantly low noise figure of this radio frequency amplifier is 0.8 dB with a typical gain of 20 dB. The output power P1dB of this LNA is 17 dBm.

LNA amplifier LNA-50M1G is rated at +20 Volts DC and 90 mA. Our low noise amplifiers are available in various configurations over different frequency bands to fit your needs, all of which shipped worldwide the same day.

Features

- Broadband: 50 MHz to 1 GHz
- Noise Figure: 0.8 dB
- P1dB: 17 dBm
- Small Signal Gain: 20 dB typical
- 50 Ohm Input and Output Matched
- -40~+85°C Operating Temperature
- Unconditionally Stable
- Single DC Positive Supply

Applications

- Laboratory Applications
- R&D Labs
- Radar Systems
- Telecom Infrastructure
- Test Instrumentation
- Communication Systems
- Wireless Communication
- Microwave Radio Systems
- Low Noise Amplifier
- General Purpose Amplification
- General Purpose Wireless
- RF Pre-amplification

Low Noise Amplifier

LNA-50M1G

50 MHz to 1 GHz, 0.8 dB NF, 17 dBm P1dB, 20 dB Gain, SMA

HZ-THZ

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.05		1	GHz
Small Signal Gain	17	20		dB
Gain Flatness		±1.0		dB
Input VSWR		1.5		: 1
Output VSWR		1.5		: 1
Noise Figure		0.8	1.5	dB
Output Power P1dB	15	17		dBm
Output 3rd Intercept Point	28	32		dBm
Operating DC Current		70	90	mA
Operating DC Voltage	+5		+20	Volts
Input Connector			SMA Female	
Output Connector			SMA Female	

Electrical Specification Notes:

Values at +25°C, sea level.

Absolute Maximum Rating

Parameter	Rating	Units
DC Voltage	+5 to +20	Volts
Operating Temperature	-40 to +70	°C
Storage Temperature	-55 to +85	°C

Low Noise Amplifier

LNA-50M1G

50 MHz to 1 GHz, 0.8 dB NF, 17 dBm P1dB, 20 dB Gain, SMA

HZ-THZ

Mechanical Specifications

Size

Length	1.88 in [47.75 mm]
Width	0.88 in [22.36 mm]
Height	0.39 in [10.00 mm]


Weight 0.38 lbs [172.00 g]

Package Type Customized

Outline Drawings

Unit: mm

Tolerance: ± 0.05 mm



How To Order

LNA-50M1G

Pls send request to sales@hz-thz.com.