Low Noise Amplifier

LNA-950M2G

950 MHz to 2 GHz, 5.0 dB NF, 18 dBm P1dB, 17 dB Gain, N

HZ-THZ

Description

LNA-950M2G low noise amplifier from HZ-THZ (also known as LNA) is featured in our extensive in-stock RF amplifier selection. Our connectorized low noise amplifier uses N connectors at 50 Ohm. HZ-THZ low noise amplifier has a minimum frequency of 950 MHz and maximum frequency of 2 GHz. The significantly low noise figure of this radio frequency amplifier is 5.0 dB with a typical gain of 17 dB. The output power P1dB of this LNA is 18 dBm.

LNA amplifier LNA-950M2G is rated at +24 Volts DC and 100 mA. Our low noise amplifiers are available in various configurations over different frequency bands to fit your needs, all of which shipped worldwide the same day.

Features

■ Broadband: 950 MHz to 2 GHz

■ Noise Figure: 5.0 dB

■ P1dB: 18 dBm

■ Small Signal Gain: 17 dB typical

■ 50 Ohm Input and Output Matched

- -40~+85°C Operating Temperature
- Unconditionally Stable
- Single DC Positive Supply

Applications

- Laboratory Applications
- R&D Labs
- Radar Systems
- Telecom Infrastructure
- Test Instrumentation
- Communication Systems

- Wireless Communication
- Microwave Radio Systems
- Low Noise Amplifier
- General Purpose Amplification
- General Purpose Wireless
- RF Pre-amplification

950 MHz to 2 GHz, 5.0 dB NF, 18 dBm P1dB, 17 dB Gain, N

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.95		2	GHz
Small Signal Gain	15	17		dB
Gain Flatness		±0.5	±1.0	dB
Input VSWR		1.0	1.67	: 1
Output VSWR		1.0	1.67	: 1
Noise Figure		5.0	10	dB
Output Power P1dB	15	18		dBm
Output 3rd Intercept Point		32		dBm
Operating DC Current		70	100	mA
Operating DC Voltage		+24	+28	Volts
Input Connector	N Female			
Output Connector	N Female			

Electrical Specification Notes:

Values at +25°C, sea level.

Absolute Maximum Rating

Parameter	Rating	Units
DC Voltage	+24 to +28	Volts
Operating Temperature	-40 to +85	${}^{\circ}\!$
Storage Temperature	-55 to +85	$^{\circ}\! \mathbb{C}$

Low Noise Amplifier

LNA-950M2G

950 MHz to 2 GHz, 5.0 dB NF, 18 dBm P1dB, 17 dB Gain, N

HZ-THZ

Mechanical Specifications

Size

 Length
 2.70 in [68.55 mm]

 Width
 1.57 in [40.00 mm]

 Height
 0.98 in [25.00 mm]


Weight 0.38 lbs [172.00 g]

Package Type Customized

Outline Drawings

Unit: mm

Tolerance: ±0.05 mm



How To Order

LNA-950M2G

Pls send request to sales@hz-thz.com.